

nex-robotics

Nex Robotics Pvt. Ltd.

Motor Controllers [_](#)



Name	Product Id	Price	Thumbnail Image	Description	Update
Super Hercules 36V, 30Amp Motor Driver	NR-MDR-S-HER-36V30A	Rs.2,576.25			

ï¿½ï¿½ï¿½ï¿½type=image,width=31.75,height=31.75ï¿½ï¿½ï¿½ï¿½
90.00 0 0 90.00
28.35 541.70 cm
/I3 Do Q

Super Hercules 36V,
30Amp Motor Driver is a
upgraded version of the
Hercules 36V, 30Amp
Motor Driver which has
better thermal
management for higher
current handling for
longer duration.

Quantity:

İçerik 1/2 İçerik 1/2 İçerik 1/2

İğ12İğ12İğ12t

İçerik 1/2 İçerik 1/2 İçerik 1/2
Add to
Cart

İçerik

i 1/2 i 1/2 i 1/2 t

İçerik 1/2 İçerik 1/2 İçerik 1/2

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

ï½ï½ï½t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İ½İ½İ½t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 İ

[Hercules](#)
[36V.](#)
[30Amp](#) NR-MDR-HER-36V30A
[Motor](#) Rs.2,238.75
[Driver](#)

ï¿½ï¿½ï¿½ï¿½type=image,width=31.75,height=31.75ï¿½ï¿½ï¿½ï¿½
90.00 0 0 90.00
28.35 527.53 cm
/l4 Do Q

Hercules 36V, 30Amp
Motor Driver is virtually
indestructible DC motor
controller capable of
driving loads up to
30Ampere at 36V.

Quantity:

ï½ï½ï½ï½ï½t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İçerik

Add to
Cart

İ Ğ 1/2İ Ğ 1/2İ Ğ 1/2İ

i½i½i½t

İçerik

123456789

İçerik

İı½İİ½İİ½İı

[Hercules](#)
[Lite 36V.](#)
[8Amp](#)
[Motor](#)
[Driver](#)

NR-MDR-LI-HER-36V8A

Rs.1,399.50

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İçerik

İçerik

Add to

Cart

1/2

١٤٢٥/١٢/٢٣

İ ½İ ½İ ½İ

ï½tï½tï½t

İ Ğ 1/2İ Ğ 1/2İ Ğ 1/2İ

İ Ğ 1/2İ Ğ 1/2İ Ğ 1/2İ

١٤٢٥/١٢/٢٣

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

[Hercules](#)
[16V,](#)
[30Amp](#)
[Motor](#)
[Driver](#)

NR-MDR-HER-16V30A

Rs.2,238.75

Hercules 16V, 30Amp
Motor Driver is virtually
indestructible DC motor
controller capable of
driving loads up to
30Ampere at 16V.

Quantity:

type=image,width=31.75,height=31.75
90.00 0 0 90.00
28.35 499.18 cm
/16 Do Q

î½î½î½t

ÿ½ÿ½ÿ½t

İ ½İ ½İ ½İ ½İ

İçerik 1/2 İçerik 1/2 İçerik 1/2
Add to
Cart

ıġ½ıġ½ıġ½t

İçerik

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İçerik 1/2 İçerik 1/2 İçerik 1/2

İğ12İğ12İğ12t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

L298 46V,
2A Stepper

Motor /
Dual DC

NR-MDR-L298-X1-46V2A Rs.198.00

Motor
Driver

İ Ğ 1 2 İ Ğ 1 2 İ Ğ 1 2 t

İ Ğ 1 2 İ Ğ 1 2 İ Ğ 1 2 type=image,width=31.75,height=31.75 İ Ğ 1 2 İ Ğ 1 2 İ Ğ
90.00 0 0 90.00

28.35 485.01 cm
/I7 Do Q

L298 46V, 2A Stepper
Motor / Dual DC Motor
Driver module from NEX
Robotics can drive
bipolar stepper motor or
Two DC motors at the
same time.

İçerikleriniz için
Notify
Me!

İçerik 1/2 İçerik 1/2 İçerik 1/2

İ ½İ ½İ ½İ

ï½ï½ï½ï½t

İçerik

İçerik

i½i½i½t

ï½ï½ï½ï½t

î ½î ½î ½î ½t

[L298 18V,
2A Dual
Stepper
Motor /
Quad DC
Motor
Driver](#)

NR-MDR-L298-X2-18V2A Rs.499.50

İ Ğ ½İ Ğ ½İ Ğ ½İ Ğ ½İ

type=image,width=31.75,height=31.75

90.00 0 0 90.00

28.35 470.83 cm

/18 Do Q

L298 18V, 2A Dual
Stepper Motor / Quad
DC Motor Driver module
from NEX Robotics can
drive two bipolar stepper
motors or 4 DC motors at
the same time.

Quantity:

İçerik

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İçerik

İçerik 1/2 İçerik 1/2 İçerik 1/2
Add to
Cart

١٤٢٥/١٢/١٤

İġ 1/2İġ 1/2İġ 1/2İġ

İ Ğ 1/2İ Ğ 1/2İ Ğ 1/2İ

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

i 1/2 i 1/2 i 1/2 t

1 2 1 2 1 2 t

İçerik 1/2 İçerik 1/2 İçerik 1/2

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

ï¿½ï¿½ï¿½ï¿½type=image,width=31.75,height=31.75ï¿½ï¿½ï¿½ï¿½
90.00 0 0 90.00
28.35 456.66 cm
/I9 Do Q

A3982 35V, 2A Stepper
Motor Driver is the most
ideal driver for the
Micromouse. It can drive
bipolar stepper motor
with full and half
stepping.

Quantity:

İçerik

İ ½İ ½İ ½İ

İ Ğ ½ İ Ğ ½ İ Ğ ½ t

İçerik 1/2 İçerik 1/2 İçerik 1/2
Add to
Cart

İçerik

i½i½i½t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

1/2 1/2 1/2 1/2

İ ½ İ ½ İ ½ t

İçerik

ï¿½ï¿½ï¿½ï¿½ï¿½

[TB66FNG](#)
[13.5V, 1A](#)
[Dual DC](#)
[Motor](#)
[Driver](#)

NR-MDR-
TB66FNG-13.5V1A

Rs.139.50

ï¿½ï¿½ï¿½ï¿½type=image,width=31.75,height=31.75ï¿½ï¿½ï¿½ï¿½
90.00 0 0 90.00
28.35 442.49 cm
/I10 Do Q

TB66FNG 13.5V, 1A
Dual DC Motor Driver is
a low cost, compact dual
DC motor driver which
can drive two DC motors Quantity:
up to 13.5V, 1A each.

İ Ğ 1/2İ Ğ 1/2İ Ğ 1/2İ

Īġ½Īġ½Īġ½t

İğ12İğ12İğ12t
Add to
Cart

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İçerik 1/2 İçerik 1/2 İçerik 1/2

İçerik

İçerik

İçerik

İçerik

İçerik

ï¿½ï¿½ï¿½ï¿½t

i½i½i½i½t

[LMD18200](#)

[55V, 3Amp](#)

[Motor](#)

[Driver](#)

NR-MDR-LMD18200-55V3A

Rs.1,499.63

ï¿½ï¿½ï¿½ï¿½type=image,width=31.75,height=31.75ï¿½ï¿½ï¿½ï¿½
90.00 0 0 90.00
28.35 428.31 cm
/l11 Do Q

The LMD18200 is a 55V,
3A Motor Driver
designed for motion
control applications. It
can handle peak current
up to 6A.

İġ1/2İġ1/2İġ1/2t

İçerikleriniz için
Notify
Me!

İçerik

ï½tï½tï½t

î Ğ ½ Ğ ½ Ğ ½ Ğ ½ t

1/2 1/2 1/2

i 1/2 i 1/2 i 1/2 t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

ï½ï½ï½ï½t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

[L293D](#)

[Motor](#)

[Driver IC](#)

L293D

Rs.84.38

ï½ï½ï½type=image,width=31.75,height=31.75ï½ï½ï½
90.00 0 0 90.00
28.35 414.14 cm
/12 Do Q

The L293D is a quadruple half H-bridge bidirectional motor driver IC that can drive current of up to 600mA with voltage range of 4.5 to 36 volts.

ٲٲٲٲٲٲٲٲٲٲ
Notify
Me!

ĩ ġ ħ ģ ĩ ĵ ĩ ĵ ĩ ĵ ĩ ĵ ĩ

Īġ1/2ġ1/2ġ1/2t

İçerik 1/2 İçerik 1/2 İçerik 1/2

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İ ½ İ ½ İ ½ t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

1/2 1/2

ĪĊ½ĪĊ½ĪĊ½t

[L298 2A](#)
[dual H](#)
[Bridge](#)
[Driver](#)

NR-L298-Multiwatt 15-DIP Rs.115.50

The L298 is a Dual Full Bridge driver that can drive up to 2Amps per bridge with supply voltage up to 46V.

Quantity:

type=image,width=31.75,height=28.575
90.00 0 0 81.00
28.35 408.97 cm
/113 Do Q

١٢٤ ١٢٤ ١٢٤

İçerik 1/2 İçerik 1/2 İçerik 1/2
Add to
Cart

ï¿½ï¿½ï¿½ï¿½ï¿½ï¿½ï¿½

İçerik

İġ ½İġ ½İġ ½İġ

İġ1/2İġ1/2İġ1/2t

İçerik 1/2 İçerik 1/2 İçerik 1/2t

28.35 385.79 cm
/114 Do Q

The L297/A/D Stepper Motor Controller IC generates four phase drive signals for two phases bipolar and four phase unipolar step motors in microcomputer-controlled applications.

ï½ï½ï½ï½ï½t

İçeriği
Notify
Me!

İçerik

İġ 1/2İġ 1/2İġ 1/2t

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

İ ½İ ½İ ½İ ½İ

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

İ Ğ 1/2 İ Ğ 1/2 İ Ğ 1/2 t

ï¿½ï¿½ï¿½ï¿½type=image,width=31.75,height=31.75ï¿½ï¿½ï¿½ï¿½
90.00 0 0 90.00
28.35 371.62 cm
/I15 Do Q

The ULN2003 is high
voltage, high current
Darlington array.

Quantity:

İçerik

İçerik

i 1/2 i 1/2 i 1/2 t

İçerik
Add to
Cart

İġ ½İġ ½İġ ½İġ

İçerik

İġ ½İġ ½İġ ½İġ

İçerik

İçerik

İġ 1/2İġ 1/2İġ 1/2t

Īġ1/2ġ1/2ġ1/2t

-
-
-
-
-

« « Start
« Prev
1
Next »
End » »

Results 1 - 13 of 13